

IT'S TIME TO STOCK UP



FEATURED PRODUCT: 10LB PURPLE K DRY CHEMICAL FIRE EXTINGUISHER

Purple K Dry Chemical is a high performance extinguishing agent most effective for dealing with flammable liquid fires. Purple K is suitable for use on Class B and Class C fires.

TYPICAL USES:

For flammable liquid hazards in public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For flammable liquid hazards in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating. Not recommended for use on sensitive electronic equipment.

SPECS:

UL/ULC Rating: 80-B:C
Temperature Range: -65° to 120°F
Discharge Time: 22 sec
Discharge Range ft (m): 15-21 (4.6-6.4)
Operating Pressure: 195 psi (1344 kPa)
Mounting Type: Wall
USCG Approval: Type B:C Size II

Part # BFE 10HISA-PK

BUCKEYE FIRE EXTINGUISHERS & BRACKETS

Willful or repeated OSHA violations (such as the lack of fire extinguishers placed in proper areas, or the use of defective fire extinguishers) can reach astronomically high fines.

Talk to your Mesa sales agent to learn more, or visit us online at www.mesaequipment.com to sign up and order today. And discover how a small investment in fire extinguishers can help protect your tools and your business.

MESA EQUIPMENT & Supply Company

www.mesaequipment.com

BUCKEYE FIRE EXTINGUISHERS & BRACKETS



BFE 13315* / 2.5 LB ABC FIRE EXTINGUISHER W/ VEHICLE BRACKET

UL/ULC Rating: 1-A:10-B:C

Temperature Range: -65° to 120°F

Discharge Time: 9 sec

Discharge Range ft (m): 9-15 (2.7-4.6)

Operating Pressure: 100 psi (689 kPa)

Mounting Type: Vehicle

USCG Approval: Type B:C Size I



BFE 10914* / 5 LB ABC FIRE EXTINGUISHER

UL/ULC Rating: 3-A:40-B:C

Temperature Range: -65° to 120°F

Discharge Time: 14 sec

Discharge Range ft (m): 12-18 (3.7-5.5)

Operating Pressure: 195 psi (1344 kPa)

Mounting Type: Wall

USCG Approval: Type A Size II; Type B:C Size I



BFE 25614* / 5 LB ABC FIRE EXTINGUISHER W/ VEHICLE BRACKET

UL/ULC Rating: 3-A:40-B:C

Temperature Range: -65° to 120°F

Discharge Time: 14 sec

Discharge Range ft (m): 12-18 (3.7-5.5)

Operating Pressure: 195 psi (1344 kPa)

Mounting Type: Wall

USCG Approval: Type A Size II; Type B:C Size I



BFE 11340* / 10 LB ABC FIRE EXTINGUISHER

UL/ULC Rating: 4-A:80-B:C

Temperature Range: -65° to 120°F

Discharge Time: 22 sec

Discharge Range ft (m): 15-21 (4.6-6.4)

Operating Pressure: 100 psi (689 kPa)

Mounting Type: Wall

USCG Approval: Type A Size II; Type B:C Size II



BFE 12120* / 20 LB ABC FIRE EXTINGUISHER

UL/ULC Rating: 10-A:120-B:C

Temperature Range: -65° to 120°F

Discharge Time: 27 sec

Discharge Range ft (m): 15-21 (4.6-6.4)

Operating Pressure: 100 psi (689 kPa)

Mounting Type: Wall

USCG Approval: Type A Size II; Type B:C Size III



5LB 5DC HD | 10LB 809 HD FIRE EXTINGUISHER BRACKETS

BFE 700224

5 lb. & 5.5 lb. Dry Chemical, Halotron & MiniGuard (horizontal)

Reference Diameter: 4.25 inches

BFE 700226

10 lb. Tall Dry Chemical, MiniGuard (horizontal) and 5 lb. CO2

Reference Diameter: 5.0 – 5.25 inches

SHOP M.R.O. PRODUCTS ON OUR WEBSITE!

Visit www.mesaequipment.com to shop for Maintenance/Repair/Operations products you need. We offer convenient online shopping and can ship your products direct to you, or have them ready for store pickup at our branch locations. Mesa also offers **FREE** local delivery service for in-stock items.

MESA ALBUQUERQUE NM BRANCH

7100 2nd Street NW
Albuquerque, NM 87107 USA
Tel: (505) 345-0284
info@mesaequipment.com

MESA EL PASO TX BRANCH

1342 Lomaland Drive
El Paso, TX 79935 USA
Tel: (915) 594-1414
epmesa@mesaequipment.com

MESA
EQUIPMENT
& Supply Company
www.MESAEQUIPMENT.COM

*AVAILABILITY SUBJECT TO STOCK ON HAND